

Revision: 2

Date: July 2018

Supersedes all previous issues

Liano Invisi II

4.5/3 litre Dual Flush Toilet Suite with Liano Wall Faced Box Rim Vitreous China Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications









Liano Invisi II

4.5/3 litre Dual Flush Toilet Suite with Liano Vitreous China Wall Faced Box Rim Pan and Invisi II Cistern for Inwall, Under Counter, Induct or Inceiling applications





A sharp, symmetrical designed wall faced concealed toilet suite comprises the **Liano** pan and trusted Caroma **Invisi II** cistern, and is targeted for commercial applications, but is also suitable for domestic use. The pan connection system includes the patented Caroma Uni-Orbital® Connector that extends to any position in a 50mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 120mm with a recommended setout of 90mm. The smooth sided pan is available in both standard and easy height models with the great looking thin lid, soft close seat with quick release. Choose from a variety of buttons from the Caroma range to complete your desired look.

Pan: Liano back inlet 4.5 litre full flush box rim pan
Traps: Universal trap for S or P-trap installations.

 Inlet:
 50mm back inlet for concealed cistern and flushvalve installation.

 Cisterns and Flushvalves:
 Invisi II cistern – suitable for inwall, under counter, induct and inceiling applications. For push button and access plate (supplied separately) options see

chapter 6.15.1 CISTERNS of the Caroma Technical Manual.

Fixing: The pan can be fixed to the floor by either bedding into mortar or using the D82

Concealed Fixing Bracket.

Seats: The **Liano** soft close toilet seat is provided as standard with the Liano suite.

A quality solid section compression moulded toilet seat, fitted with buffers and

metal hinges.

Colours: White only.

Installation: The installation of the toilet suite shall be in accordance with the normal minimum

drainline grade requirements in AS/NZS 3500.2.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing

variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications

without notice.

